








































Bifold Window Specifications

- Glazing in windows complies with AS 1288. Wind Region A. Exposed Suburban
- Purchaser to specify if window conditions vary from this
- These products are designed to 1000pa wind pressure and 150pa water pressure
- All frames are viewed from the outside. Items as below are open out only

| STUD OPENING | FRAME | 935 | 1230 | 1230 | 1530 | 1830 | |
|--------------|-------|--|--|--|--|---|--|
| | | 915 | 1210 | 1210 | 1510 | 1810 | |
| 1077 | 1057 |  BW22R1009 |  BW22R1012 |  BW33R1012 |  BW33R1015 |  BW33R1018 | |
| | | 1570 1550 | 1570 1550 | 1830 1810 | 1830 1810 | 2420 2400 | 2420 2400 |
| 1077 | 1057 |  BW44R1015 |  BW42L2R1015 |  BW44R1018 |  BW42L2R1018 |  BW44R1024 |  BW42L2R1024 |
| | | 935 915 | 1230 1210 | 1230 1210 | 1530 1510 | 1830 1810 | |
| 1217 | 1197 |  BW22R1209 |  BW22R1212 |  BW33R12152 |  BW33R1215 |  BW33R1218 | |
| | | 1570 1550 | 1570 1550 | 1830 1810 | 1830 1810 | 2420 2400 | 2420 2400 |
| 1217 | 1197 |  BW44R1215 |  BW42L2R1215 |  BW44R1218 |  BW42L2R1218 |  BW44R1224 |  BW42L2R1224 |
| | | 935 915 | 1230 1210 | 1230 1210 | 1530 1510 | 1830 1810 | |
| 1417 | 1397 |  BW22R1409 |  BW22R1412 |  BW33R1412 |  BW33R1415 |  BW33R1418 | |
| | | 1570 1550 | 1570 1550 | 1830 1810 | 1830 1810 | 2420 2400 | 2420 2400 |
| 1417 | 1397 |  BW44R1415 |  BW42L2R1415 |  BW44R1418 |  BW42L2R1418 |  BW44R1424 |  BW42L2R1424 |
| | | 935 915 | 1230 1210 | 1230 1210 | 1530 1510 | 1830 1810 | |
| 1517 | 1497 |  BW22R1509 |  BW22R1512 |  BW33R1512 |  BW33R1515 |  BW33R1518 | |
| | | 1570 1550 | 1570 1550 | 1830 1810 | 1830 1810 | 2420 2400 | 2420 2400 |
| 1517 | 1497 |  BW44R1515 |  BW42L2R1515 |  BW44R1518 |  BW42L2R1518 |  BW44R1524 |  BW42L2R1524 |
| | | 935 915 | 1230 1210 | 1230 1210 | 1530 1510 | 1830 1810 | |

These configurations / sizes are provided as a guide. Southern Star can manufacture this product to suit most openings. Optional "wind down" flywire screens are available with this product. Lockable hardware is standard. Options are only available at time of ordering. Please note: Some frames may require doors or sashes removed upon delivery and or onsite glazing depending on size.

Bifold Windows are available with the following sill options

- 1 Standard sill with threshold
- 2 Standard sill no threshold*
- 3 No sill*
- 4 Extended sill with threshold
- 5 Extended sill no threshold.*

* These options are not available on 3 panel and 4 panel one way Bifold Windows. Benchtop is 400mm as standard.



1 Standard 2 Colonial Bar 3 Heritage Bar

NOTE: Substitute "L" for "R" when ordering left-handed options.



Our commitment to continual product development necessitates that sizes and specifications may change without notice.

