


# Trislide Door Specifications

- Glazing in windows complies with AS 1288. Human Impact Requirements
- Purchaser to specify if door conditions vary from this
- These products are designed to 1000pa wind pressure and 240pa water pressure
- All frames are viewed from the outside

STUD OPENING		2250	2420	2725	3620	4420
FRAME		2230	2400	2705	3600	4400
2127	2107					
		TS2122R3	TS2124R3	TS2127R3	TS2136R3	TS2144R3
		2250	2420	2725	3620	4420
		2230	2400	2705	3600	4400
2417	2397					
		TS2422R3	TS2424R3	TS2427R3	TS2436R3	TS2444R3
		4420	5220	5720		
		4400	5200	5700		
2127	2107					
		TS2144-6	TS2152-6	TS2160-6		
		4420	5220	5720		
		4400	5200	5700		
2417	2397					
		TS2444-6	TS2452-6	TS2460-6		

These configurations / sizes are provided as a guide. Southern Star can manufacture this product to suit most openings. Lockable hardware is standard. Options are only available at time of ordering. Please note: Some frames may require doors or sashes removed upon delivery and or onsite glazing depending on size.



1 Standard 2 Colonial Bar 3 Colonial Bar 4 Heritage Bar 5 Federation Bar



Our commitment to continual product development necessitates that sizes and specifications may change without notice.

